



The IBUC Advantage

All IBUCs are equipped with cutting-edge intelligent technology:

- Highest quality & exacting performance guaranteed through individual unit testing over temperature
- Superior linearity for maximum useable output power
- Amplifier overdrive protection
- User-selectable AGC/ALC for optimal performance & compatibility with modem adaptive coding
- New high capacity microprocessor & extended M&C functions
- Weatherized RJ45 Ethernet interface for simplified connection

ULTIMATE MANAGEMENT & CONTROL

- » Local Web Interface & NMS-Friendly SNMP «
- » 70+ User Configurable Thresholds & Alarms «
- » Upgraded Event Log with 1,000 Sensor Readings «
- » Performance Trend Analysis Tools & Statistical logs «
- » Embedded Web Pages for Universal Web Browser Access «

C-Band IBUC G

200W GaN IBUC for multicarrier application.



New **Cyber Hardened** version available

Multicarrier Application

200W
 P_{Lin} 100W

GaN Tech Amplifier

3 Year Warranty

Applications

The new IBUC **G** now supports multicarrier transmission across the full C-band spectrum. The IBUC **G** delivers the highest available output power, making it an ideal solution for high data rate multicarrier applications such as maritime, broadband, broadcast and network hubs.

Gallium Nitride amplifier technology enables smaller packaging for antenna mounting, eliminating the losses in long waveguide runs. And the greater power efficiency translates to an appreciable reduction in power consumption. Comparing favorably with earlier technology TWTAs, the GaN IBUC **G** delivers maximum linear output power with the reliability of solid state.

Options

- 1+1 Transmit Redundancy with Eco-Mode
- High Stability Internal 10 MHz Reference with Auto-Detection
- Mounting Brackets
- N-Type, F-Type or TNC Input Connectors
- Handheld Terminal
- Cyber Hardened
- WGS (Wideband Global SATCOM) compatible.

Note: Since not all the optional features can be combined, please, contact our sales team for further info at: Sales@Terrasatinc.com

C-Band 200W IBUC G | Multicarrier Application

Frequency Range	RF (MHz)	IF (MHz)	
Sense		Inverting	Non-Inverting
Band 1 Std C	5850 to 6425	950 to 1525	950 to 1525
Band 2 Palapa	6425 to 6725	975 to 1275	1125 to 1425
Band 3 Insat	6725 to 7025	1150 to 1450	965 to 1265
Band 4 Ext C	5850 to 6650	950 to 1750	950 to 1750
Band 5 Full C	5850 to 6725	975 to 1850	950 to 1825

Input

VSWR/ Impedance	1.5:1 / 50 Ohm	
Input Connector	Type N Female (50 Ohm)	
Input Connector Options	Type F (75 Ohm), TNC (50 Ohn)	
Input Power Detector Range options:	Standard Version -55 to -20 dBm	WGS Version -35 to 0 dBm

Gain

Small Signal Gain (L-band to RF) with attenuator set to 0 dB options:

200W	Standard Version 84 dB min	WGS Version 73 dB min
Attenuator Range	30 dB variable in 0.1 dB steps	
Gain Flatness	Full Band	4 dB p-p max
	36 MHz	1.5 dB p-p max
	1 MHz	0.25 dB p-p
Gain Variation Over Temperature	Bands 1/2/3	Bands 4/5
Open Loop	3 dB p-p max	4 dB p-p max
With AGC	1 dB p-p max	1 dB p-p max

RF Output

Interface	CPR-137G
VSWR	1.3:1 max

Output Power

	200W	
	Band 1	Bands 2/3/4/5
at P_{Sat} (typ)	53 dBm	52.5 dBm
at P_{Lin} (min)	50 dBm	49.5 dBm
19 dB min of NPR (Noise Power Ratio) at:	47 dBm	46.5 dBm

P_{Lin} is the maximum linear power as defined by MIL STD 188-164C
Two-tone measured at 5MHz and 150 MHz spacing

Level stability with ALC	± 0.5 dB
Output power detector range	Rated power to -20 dB
Power reading accuracy	± 1.0 dB max.
Spurious @ P_{Lin}	
In Band	-70 dBc
Out of Band	Complies with EN 301 443 & MIL-STD 188-164C
Harmonics @ P_{Lin}	-50 dBc max.
Output Noise Power Density	
Tx <	- 73 dBm/Hz
Rx <	- 145 dBm/Hz

SSB Phase Noise	External Reference	IBUC G
10 Hz	-115 dBc/Hz	-54 dBc/Hz
100 Hz	-140 dBc/Hz	-79 dBc/Hz
1 KHz	-150 dBc/Hz	-89 dBc/Hz
10 KHz	-155 dBc/Hz	-94 dBc/Hz
100 KHz	N/A	-100 dBc/Hz
1 MHz	N/A	-110 dBc/Hz

External Reference (Multiplexed on TX IFL)

Frequency & Level	10 MHz	-12 to +5 dBm
-------------------	--------	---------------

Internal Reference- Optional

Local Oscillator Frequency

	Sense	Inverting	Non-Inverting
Band 1		7375 MHz	4900 MHz
Band 2		7700 MHz	5300 MHz
Band 3		8175 MHz	5760 MHz
Band 4		7600 MHz	4900 MHz
Band 5		7700 MHz	4900 MHz

IBUC Power Supply

Voltage	100 to 240 VAC 50 Hz / 60 Hz	
Power Consumption	Band 1	Bands 2/3/4/5
	<u>200W</u>	<u>200W</u>
	at P_{Sat}	950 VA 925 VA
	at P_{Lin}	750 VA 725 VA

Monitor & Control - For Standard Versions

Ethernet (HTTP, Telnet, SNMPv2c) via RJ45 Connector
RS232/485, Handheld Terminal via MS-Type Connector
 FSK multiplexed on TX IFL

Monitor & Control - For Cyber Hardened Versions

Ethernet (HTTPS, SSHv2, SNMPv3 with USM and VACM) via RJ45 Connector
RS232 via MS-Type Connector
 XSS (Cross Site Scripting)
 Two NTP Servers Providing Redundancy
FIPS 140-2 compatible.

The Cyber Hardened versions have embedded new high-end Cyber Security features, from hardware to software, including a new controller board and the new firmware. For further details, refer to the Cyber Hardened IBUCs' datasheet at www.terrasatinc.com/products/

Environmental

Operating Temperature	-40°C to +55°C
Relative Humidity	100% Condensing
Altitude	10,000 ft (3,000 m) ASL

Mechanical

Weight	33 lbs 14.9 kg
Size	16.2 x 10 x 7.6 in. 411 x 254 x 193 mm

(Dimensions not including isolators)

Specifications subject to change without notice. Updated: September 12th 2023



Questions? Contact Us
 +1 (408) 782 5911
Sales@Terrasatinc.com

315 Digital Drive
 Morgan Hill, CA 95037
www.Terrasatinc.com